



ÜRÜN KODU/PRODUCT CODE	: 801X06
ÜRÜN ADI/PRODUCT NAME	: 60W YOL VE CADDE AYDINLATMASI/60W STREET LIGHT
ÜRÜN BİLGİSİ/PRODUCT INFORMATION	
GÖVDE/BODY	: ALÜMİNYUM ENJEKSİYON/DIE CAST ALUMINIUM
CAM/GLASS	: TEMPERLİ CAM/TEMPERED GLASS IK08
IP KORUMA SINIFI/IP PROTECTION	: IP66-CLASS I
KULLANIM ŞEKLİ/FIELDS OF APPLICATION	: YOL VE CADDE AYDINLATMA/ROAD AND STREET LIGHTING
LED	: SMD MID POWER

801X06	→ Işık Rengi/Light Color	X=3 3000K	4 4000K	6 6500K
--------	--------------------------	-----------	---------	---------

ELEKTRİKSEL ÖZELLİKLER/ELECTRICAL SPECS

TÜKETİM GÜCÜ/POWER	: 60W
GİRİŞ GERİLİMİ/INPUT VOLTAGE	: AC 220V
GİRİŞ AKIMI/INPUT CURRENT	: 0.2 A
FREKANS/FREQUENCY	: 50 Hz
GÜÇ FAKTÖRÜ/POWER FACTOR	: 0.95
ÇIKIŞ GERİLİMİ/OUTPUT VOLTAGE	: DC25-42V
ÇIKIŞ AKIM/OUTPUT CURRENT	: 1.4 A
THD(TOTAL HARMONIC DISTORTION)	: <%20

FOTOMETRİK ÖZELLİKLER/PHOTOMETRIC SPECS

RENK SICAKLIĞI/KELVIN TEMPERATURE(CCT)	: 3000K	4000K	6500K
IŞIK AÇISI/LIGHT BEAM ANGLE	: 120°		
IŞIK AKISI/LUMEN	: 5630	5930	5930
RENKSEL GERİ VERİM/COLOR RENDERING INDEX (CRI)	: Ra>80		
VERİM/EFFICIENCY	: 113Lm/W		

DİĞER ÖZELLİKLER/OTHER SPECS

ÇALIŞMA SICAKLIĞI/OPERATING TEMPERATURE(CCT)	: -30°C, 50°C
LED ÖMRÜ/LED LIFE TIME (PERFORMANCE L70)	: ≥54.000 Saat/Hours

OPSİYONEL ÖZELLİKLER/OPTIONAL SPECS

SİMETRİK 30°-60°-90°/SYMMETRIC 30°-60°-90°	: ✓
ASİMETRİK 157°x70°/ASYMMETRIC	: ✓
ZAMAN AYARLI DIM/ TIMER DIMMING	: ✓
0-10V DIM	: ✓
DALI DIM	: ✓

FOTOMETRİK EĞRİ/LIGHT DISTRIBUTION CURVE

Işık Dağılım Eğrisi/Light Distribution Curve

