



Suspended Linear LED lighting 75x90

Housing

Eloxal coating extrusion aluminum

Diffuser

Polycarbonate Opal

LED

SMD LED with high color rendering (Ra≥80) with a minimum lifetime of 50,000 hours (L70-85°C)

Option

- Emergency Lighting Kit(1 or 3 hours)
- DIM / DALI DIM



Product Name	Order Code	Power(W)	CCT(K)	Luminous Flux(lm)	CRI	Voltage V/Hz	Weight
Suspended Linear 600mm	240366-P	18W	3000K	855 lm	>80	220VAC	1,25 Kg
Suspended Linear 600mm	240466-P	18W	4000K	900 lm	>80	220VAC	1,25 Kg
Suspended Linear 600mm	240666-P	18W	6500K	945 lm	>80	220VAC	1,25 Kg
Suspended Linear 600mm	240367-P	27W	3000K	1280 lm	>80	220VAC	1,25 Kg
Suspended Linear 600mm	240467-P	27W	4000K	1350 lm	>80	220VAC	1,25 Kg
Suspended Linear 600mm	240667-P	27W	6500K	1420 lm	>80	220VAC	1,25 Kg
Suspended Linear 1200mm	240361-P	36W	3000K	1710 lm	>80	220VAC	2,59 Kg
Suspended Linear 1200mm	240461-P	36W	4000K	1800 lm	>80	220VAC	2,59 Kg
Suspended Linear 1200mm	240661-P	36W	6500K	1890 lm	>80	220VAC	2,59 Kg
Suspended Linear 1200mm	240362-P	54W	3000K	2565 lm	>80	220VAC	2,59 Kg
Suspended Linear 1200mm	240462-P	54W	4000K	2700 lm	>80	220VAC	2,59 Kg
Suspended Linear 1200mm	240662-P	54W	6500K	2835 lm	>80	220VAC	2,59 Kg
Suspended Linear 1500mm	240368-P	54W	3000K	2565 lm	>80	220VAC	2,73 Kg
Suspended Linear 1500mm	240468-P	54W	4000K	2700 lm	>80	220VAC	2,73 Kg
Suspended Linear 1500mm	240668-P	54W	6500K	2835 lm	>80	220VAC	2,73 Kg

