DESIGNTAK® - gör entré

Maintenance & mounting of your canopy

V19-5

Applies to all Designtak (Sheet Metal, Glas, Aluminum, SS)

Mounting

- Avoid walking on the roof
- After mounting flush the canopy with water and clean thoroughly. Drill cuttings and loose fasteners can cause rust formation
- Fit lace guard if needed
- Make sure no loose objects can fall on the roof
- Electrical installations may only be carried out by qualified electrician

Disclaimer

Designtak i Småland AB disclaim all responsibility for mounting and improper installation of the canopies

Maintenance

- Always scoop off the roof when there is about 15cm of snow on it
- Never hang or climb on the canopy
- When painting, follow the color trader's recommendations
- For glass roofs, immediately remove stains that can become permanent, such as basic substances

Maintenance must be done and documented twice a year, spring and autumn in order for the guarantee to apply

- Make sure the gutter and roof are kept clean from dirt, leaves etc.
- Check the density between facade and ceiling once a year. Change if necessary.
- Make sure no loose objects can fall on the roof.
- Stainless steel can be cleaned with window cleaners that do not contain chlorides (salt)

Maintenance glasscanopies

- Use a soft damp cloth on glass surface and edges. In case of severe soiling, use a mild dish soap.

Never use!

- Liquids containing ammonia or alkaline detergents
- Solvents, alcohol or bleech
- Liquids containing abrasives or having an abrasive effect
- Coarse or scratching cleaning sponges, scouring powder, steel wool, brushes, razor blades or other powerful tools

Warranty

The warranty period is 5 years counted from the delivery date from Designtak in Småland AB.

Date	Cleaning type / Cleaning liquid	Signature