


AF COVER STRING

Fireproof cupels for small service installation penetrations



DESCRIPTION

AF COVER STRING is certified to protect small service installation penetrations in false ceilings, including electrical cables, corrugated pipes, suspension chains, threaded rods.

AF COVER STRING is a rock-wool cylinder covered with aluminium foil with a longitudinal cut that enables its opening.

DIRECT APPLICATION

Mixed systems in REI mineral fibre false ceilings

Mixed systems in EI membrane false ceilings

FEATURES

Appearance:	cylindrical rock-wool element covered with aluminium
Inside diameter:	30 mm
Outside diameter:	70 mm
Height:	50 mm
Weight:	16 g/pc

PACKAGING AND STORAGE

Cardboard boxes

The product remains unaltered if stored in a closed environment away from humidity and direct exposure to atmospheric agents.

APPLICATION METHOD

1. place AF COVER STRING around the element to be protected in the false ceiling;
2. place the element in the false ceiling;
3. inject the **AF SEAL W** sealant into the cylinder until it is filled.

SPECIFICATION

Supply and application of AF COVER STRING fireproof protections consisting of an aluminised rock wool cylinder and AF SEAL W fireproof sealant for REI 120 requalification of fireproof composite and EI 120 membrane false ceilings containing small penetrations.

CERTIFICATIONS

Class REI 120 (UNI EN 1365-2)	<i>reinforced concrete floor protected by a fibre false ceiling</i>
Class EI 120 (UNI EN 1366-3)	<i>membrane false-ceiling</i>

