

ABINGDON

FLOORING

CARPET SPECIFICATION SHEET

ULTRA

Product Type	CUT	STANDARD
Product Codes	13964 4m 13965 5m	
Pile Content	100% Polypropylene	BS 4407 73/44/IEEC
Gauge	1/10	BS 4223 ISO 8543
Tuft Density	1812	BS 4223 ISO 8543
Pile weight	1550	BS 4223 ISO 8543
Pile Height	8.00	BS 4223 ISO 1766
Total Thickness	10.00	BS 4051 ISO 1765
Total weight	2456	BS 4223 ISO 8543
Product Width	4.00 /5.00	BS EN ISO 14159
Primary Backing	Woven Polypropylene	
Secondary Backing	Woven Polypropylene Fleece	BS EN 1307
Luxury Class	LC5	
Appearance Retention	4	BS ISO 10361
4000 Cycles Hexapod	3	BS ISO 10361
Classification	HEAVY DOMESTIC 23 GENERAL COMMERCIAL 32	BS EN 1307 BS EN 1307
Colour Fastness		
Light	5	BS EN 105-B02
Rubbing	4 - 5	BS ISO 105 -X12
Water	4	BS EN ISO 105-E01
Static Load	84.27%	BS 4939 ISO 3416
Dynamic Load	84.35%	BS ISO 2049
Flammability		
Methenamine Pill	PASS	BS 6307 ISO 6925
Hot Nut	N/A	BS 4790
UK Class Radiant Panel	Class F	EN 13501-1
Thermal Resistance	1.66	BS 4745 ISO 5085
Sound Absorption Coefficient	N/A	BS EN ISO 354 BS EN 20354 BS EN 11654
Pattern Repeat (cm)	N/A	BS 14159
	N/A	BS 14159
	N/A	BS 14159
Warranty		
Wear	10 YEARS	
Stain	LIFETIME	

COLOURWAYS

WHITE WHISPER	OAT	PLATINUM
MANOR HOUSE	ANTIQUE CREAM	CLOUD BURST
PARCHMENT	COUNTRY BIEGE	COCOA CREAM
ICE DANCE	SUMMER BREEZE	JADE
SOFT SHADOW	STORM	MOSS
FRENCH GREY	POWDER	RUBY
GUNMETAL	STONE WHITE	WEDGEWOOD
DOLOMITE	FROST	HAMPTON

* All Results Are Produced From Testing Of Representative Production Samples And As Such Are Subject To Normal Tolerances Within Manufacturing

					
EN 14041:2004 13	POLYPROPYLENE	CLASS 23 DOMESTIC HEAVY	CLASS 32 COMMERCIAL GENERAL	REACTION TO FIRE Ffl	NPD
					
THERMAL CONDUCTIVITY	LUXURY CLASS LC5	LIGHT FASTNESS	STAIN RESISTANCE	PCP BELOW DETECTION LIMIT	FORMALDEHYDE HAS NOT BEEN ADDED