ATLANTIS

CARPET SPECIFICATION SHEET

Product Type	**LOOP**			**STANDARD**	
Product Codes	**14607 4m** **14608 5m**				
Pile Content	**100% Polypropylene**			**BS 4407 73/44/EEC**	**INTERNAL**
Gauge	**1/4**			**BS 4223 ISO 8543**	**INTERNAL**
Tuft Density	**275**	**tuft / dm²**	**.+/-5%**	**BS 4223 ISO 8543**	**INTERNAL**
Pile weight	**1356**	**grms sq mtr**	**.+/-5%**	**BS 4223 ISO 8543**	**INTERNAL**
Surface Pile Thickness	**5.70**	**mm**		**BS 4223 ISO 1766**	
Total Thickness	**10.90**	**mm**		**BS 4051 ISO 1765**	
Total weight	**2312**	**grms sq mtr**		**BS 4223 ISO 8543**	
Product Width	**4.00/5.00**			**BS EN ISO 14159**	**INTERNAL**
Primary Backing	**Woven Polypropylene**				
Secondary Backing	**Woven Polypropylene 24 Pick Fleece**				
Luxury Class	**LC3**			**BS EN 1307**	
Appearance Retention					
4000 Cycles Hexapod	**4**			**BS ISO 10361**	
12000 Cycles Hexapod	**3**			**BS ISO 10361**	
Classification	**HEAVY DOMESTIC**		**23**	**BS EN 1307**	
	GENERAL COMMERICAL		**32**	**BS EN 1307**	
Colour Fastness					
Light	**6**			**BS EN 105-BO2**	
Rubbing	**5**			**BS ISO 105 -X12**	
Water	**5**			**BS EN ISO 105-E01**	
Static Load	**78%**	**Recovery**		**BS 4939 ISO 3416**	
Dynamic Load	**74%**			**BS ISO 2049**	
Flammability					
Methenamine Pill	**Pass**			**BS 6307 ISO 6925**	
Hot Nut	**N/A**			**BS 4790**	
UK Class Radiant Panel	**CLASS E**			**EN 13501-1**	
Thermal Resistance	**1.68**	**Tog**		**BS 4745 ISO 5085**	
Sound Absorption Coefficient	**N/A**			**BS EN ISO 354** **BS EN 20354** **BS EN 11654**	
Pattern Repeat (cm)	**N/A**	**Length**		**BS 14159**	
	N/A	**Width**		**BS 14159**	
	N/A	**Drop**		**BS 14159**	
Warranty					
Wear	**10 YEARS**				
Stain	**LIFETIME**				

COLOURWAYS

SANDSHELL	**SAND DOLLAR**	.	.
SAND	**ALMOND BISQUE**	.	.
MUSHROOM	**EGGSHELL**	.	.
FOG	**WHITE SWAN**	.	.
CRÈME	**PEARLED IVORY**	.	.
PARCHMENT	**SKIMMING STONE**	.	.
WARM TAUPE	.	.	.
CAPPUCCINO	.	.	.

*** All Results Are Produced From Testing Of Representative Production Samples And As Such Are Subject To Normal Tolerances Within Manufacturing**

0	T	2	4	V	5
EN 14041:2004	**POLYPROPYLENE**	**CLASS 23 DOMESTIC HEAVY**	**CLASS 32 COMMERICAL GENERAL**	**REACTION TO FIRE 'Efl**	**NPD**

	N	K	m	1	Z
THERMAL CONDUCTIVITY	**LUXURY CLASS LC3**	**LIGHT FASTNESS**	**STAIN RESISTANCE**	**PCP BELOW DETECTION LIMIT**	**FORMALDEHYDE HAS NOT BEEN ADDED**

Solent Wholesale Carpet Company