

Central Lubrication fitted as standard for quick and effective maintenance

Anti - Scalping Roller fitted as standard to reduce the risk of turf damage when cutting tightly on uneven surfaces.

Height Control is by means of fully pivoting castor wheels fitted with solid rubber tyres. Adjustment of cutting height between 25 and 100 mm (1"-4") is provided by movable spacers

Category 1 & 2 Linkage to fit a wide range of tractor sizes

Fully Enclosed Rear deflects cut material and any solid objects downwards to minimise the risk to bystanders.

Pivoting Top Link Bracket with slotted pin mounting allows the machine to follow ground contours to produce an even finish.

Rotor Spindles are mounted in shielded re-greasable bearings for long life and easy maintenance.

Aerodynamically Designed Blades made from hardened and tempered spring steel, give good lift, effective cutting and an even spread of cut material.







A Mulching Kit is available to produce extra chopping and even spreading. The kit comprises additional special mulching blades and housing enclosures to retain the grass until it is finely chopped

Rotor Drive is through easily tensioned B - Section vee belts. Jacking screws are used on the gear-box for the inner belts and on the idler pulleys for the outer belts.

Specifications	
Cutting Width	2.48 m (8' 2 ")
Overall Width	2.58 m (8 ' 6")
Cutting Height	25 - 100 mm
No. of Rotors	5
Rotor Overlap	22 mm
Cutting Tip Speed	100 m/sec
Weight	385 kg (850 lb)
Min. Tractor Size	25 kw (30 hp)

The Company's policy is one of continuous improvement and development, therefore specifications are subject to change without notice.