

Level indicators Window Sight glasses

Reflection and transparency glasses
For level indicator box



Mica shield
For level indicator box



Mod. 066

- Type:
 Reflection: A 5 prisms 0 to IX
 B 5 prisms 0 to IX
 H 5 prisms 0 to IX
 Transparency: A V to IX
 B V to IX
 H V to IX
- Material: ■ Borosilicate
■ Klingerit cardboard type (Joint)
■ Graphite (Joint)

For visual checking of the level of liquids in all types of vessel, including those under pressure, in special thermal and chemical conditions. Also for checking processes. The quality of the sight glass satisfies the most demanding safety standards and industry guarantees in general.

Depending on version



+243°C



100,00 bar



Steam/Gases/Liquids

Mod. 066-PM

- Type: A I to X
 B/H I to X
 Material: ■ Natural muscovite mica

In combination with transparent glasses the life of these is increased when working at high pressures and temperatures. Also, they are protected from erosion, which results from the effects of the corrosive chemical components, alkaline solutions, boiler water, steam, caustic products, hydrofluoric acids, hot and concentrated phosphoric acids, sodium and potassium hydroxides and other contaminating, viscous or corrosive media.

Applicable in level indicators for electrical generation plants, thermal power plants, petroleum refineries, petrochemical plants, pressure vessels, fertilizers, sugar refining plants, paper mills,... etc..

Depending on version



+600°C



392,00 bar



Steam/Gases/Liquids