

# Level indicators Window Sight glasses

## Window sight glasses



Model 265



Model 365



Model 366



## Transparency round glasses

### For window sight glasses



## Mod.265 EN ASME/FNPT ASME/SW

Connection: Female thread GAS  
Female thread NPT  
Socket welding ends SW  
R: 1/2" to 1"  
Material:  Cast steel. PN-40  
 Stainless steel. PN-40

## Mod.365 EN ASME/FNPT ASME/SW

Connection: Female thread GAS  
Female thread NPT  
Socket welding ends SW  
R: 1/2" to 2"  
Material:  Cast steel. PN-40  
 Stainless steel. PN-40

## Mod.366 EN ASME/ANSI

Connection: Flange x Flange  
DN: 15 to 200  
Material:  Cast steel. PN-16. PN-40  
 Stainless steel. PN-40

To verify the flow, direction and condition of liquid in a section of piping. It helps detect blockages in valves, filters and other line equipment. In particular, it enables verification of correct operation of the condensate traps, ensuring that there are no steam leaks, with the cost this would entail. It also enables observation of a product's viscosity, turbidity and, in particular, its colour in the different phases of its production process. Applicable to: piping conveying liquids, steam and condensates, among others, in any type of industry: chemical, petrochemical, pharmaceutical, food and more.

Depending on version



-60°C to +280°C



40,00 bar



Steam/Gases/Liquids

## Mod. 006

Type: Transparency 45x10  
63x10  
63x15  
80x12  
80x20  
100x15  
100x25  
125x20  
125x30  
150x25  
150x30  
175x25  
175x30  
200x30  
250x30

Material:  Borosilicate  
 Graphite (Joints)

For visual checking of the level of liquids in all types of vessel, including those under pressure, in special thermal and chemical conditions. Also for checking processes. The quality of the sight glass satisfies the most demanding safety standards and industry guarantees in general.

Depending on version



+300°C



40,00 bar



Steam/Gases/Liquids