

Normal safety valve with spring loading (AN)



AP

ES

Mod. 295 EN

- Connection: Male thread x Female thread  
 MR1 x FR2: 1/2"x1" to 1 1/4" x 2"
- Material: ■ Bronze. PMS-25 bar  
■ Carbon steel. PMS-25 bar  
■ Stainless steel. PMS-25 bar
- Seal: ○ PTFE (Teflon)  
○ Silicone's rubber  
● Fluorelastomer (Viton)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open, at the first proportional to the pressure increase, and after instantly and totally.  
 Design in accordance with "International Standard ISO 4126 -1 Safety Valves".

Depending on version



AP

ES

Mod. 296 EN

- Connection: Flange x Flange  
 DN1 x DN2: 15x25 to 32x50
- Material: ■ Bronze. PMS-25 bar  
■ Carbon steel. PMS-25 bar  
■ Stainless steel. PMS-25 bar
- Cierre: ○ PTFE (Teflon)  
○ Silicone's rubber  
● Fluorelastomer (Viton)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open, at the first proportional to the pressure increase, and after instantly and totally.  
 Design in accordance with "International Standard ISO 4126 -1 Safety Valves".

Depending on version

