

Thermostatic steam trap



443

444

543

Mod. 443 EN ASME/FNPT ASME/SW

Connection: Female thread GAS
 Female thread NPT
 Socket welding ends SW
 R: 1/4" to 1"
 Material: Stainless steel. PMS-22 bar
 Seal: Metal

Mod. 444 EN ASME/ANSI

Connection: For placing between flanges
 DN: 15 to 25
 Material: Stainless steel. PMS-22 bar
 Seal: Metal

Mod. 543 EN ASME/FNPT

Connection: Female thread GAS
 Female thread NPT
 R: 1/2"
 Material: Stainless steel. PMS-22 bar
 Seal: Metal

To extract saturated or super-heated medium or low-pressure steam condensates.

Applicable to: steam piping, irons, laundries, vessels with condensate discharge, cooking pots, sterilizers, heat exchangers, multiple dish presses, vulcanizing autoclaves, calendars, pressure reducing equipment, etc.

Depending on version



Ultrasonic leak detector



Mod. 003

Material: ABS plastic - Stainless steel

To detect leaks:
 - In condensate purgers.
 - In valve seals.

Checking for wear on bearings.
 Solving mechanical problems in general.
 Ultrasound is directional and localisable. In a noisy environment we can remove or block the distorting ultrasounds.
 During preventive maintenance, we should place the stethoscope properly and we will detect, audibly and visually, the leaks that are affecting us. We can take corrective action, safeguarding the environment, saving energy, time and consequently money.

It meets and exceeds the requirements of ASTM E1002-2005 for Leak Detection.

Depending on version

