

Round-dowel level indicator



Mod. 666 EN ASME/ANSI
Level gauges

Connection: Flange
 DN: 20 and 25
 Material: ■ Cast steel. PN-16
 ■ Cast steel. PN-40
 ■ Stainless steel. PN-40
 Seal: ● Metal
 Blowoff valve: Mod. 999 3/8" with simple joint plug

Square-dowel level indicator



Mod. 466 EN ASME/ANSI
Level gauges

Connection: Flange
 DN: 20 and 25
 Material: ■ Cast steel. PN-16
 ■ Cast steel. PN-40
 ■ Stainless steel. PN-40
 Seal: ● Metal

Mod.166-ER EN ASME/ANSI
Round-dowel level indicator box

Connection: Round-dowel Ø 20 mm.
 Box n°: 0 to X
 Material: ■ Cast steel. PN-16. PN-40
 ■ Stainless steel. PN-40

For use in boilers, receivers, cisterns, reservoirs, ...etc., to control the level of liquids, gases and steam.
 A multiple-slot polyprismatic viewer allows the level to be optically read, clearly differentiating liquid and gas phases from liquid ones.

Depending on version



Mod.166-EC EN ASME/ANSI
Square-dowel level indicator box

Connection: Square-dowel \varnothing 18 mm.
 Box n°: 0 to X
 Material: ■ Cast steel. PN-16. PN-40
 ■ Stainless steel. PN-40
 Blowoff valve: Mod. 999 3/8" with simple joint plug

For use in boilers, receivers, cisterns, reservoirs, ...etc., to control the level of liquids, gases and steam.
 A multiple-slot polyprismatic viewer allows the level to be optically read, clearly differentiating liquid and gas phases from liquid ones.

Depending on version

