



EP

AP

ES

CP

EP

AP

ES

CP

### Mod. 486 ASME

### Mod. 485 ASME

Connetion: Flange x Flange  
 NPS1 x NPS2: 1"x 2" to 8"x10"  
 Material:  Carbon steel. 150 lbs and 300 lbs  
 Stainless steel. 150 lbs and 300 lbs  
 Seal:  Metal

Connetion: Female thread NPT x Female thread NPT  
 FNPT1 x FNPT2: 3/4"x1 1/4" and 1"x1 1/2"  
 Material:  Carbon steel. 300 lbs  
 Stainless steel. 300 lbs  
 Seal:  Metal

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
 Design in accordance with "ASME code section VIII".  
 Materials according ASME code section II and ASTM.  
 Connections according ASME B1.20.1 standard.

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
 Design in accordance with "ASME code section VIII".  
 Materials according ASME code section II and ASTM.  
 Connections according ASME B1.20.1 standard.

Depending on version



Depending on version

