



CP

EP

AP

ES

AS

EP

AP

ES

AS

### Mod. 695 EN

### Mod. 685 ASME

Connection: Male thread x Female thread  
MR1 x FR2: 3/8"x1/2" to 1"x1"

Material: ■ Bronze. PMS-36 bar  
■ Stainless steel. PN-40

Seal: ○ PTFE (Teflon)  
● Silicone's rubber  
● Fluorelastomer (Viton)

Connection: Male thread NPT x Female thread NPT  
MNPT1 x FNPT2: 3/8"x1/2" to 1"x1"

Material: ■ Bronze. PMS-522, 14 psi  
■ Stainless steel. 300 lbs

Seal: ○ PTFE (Teflon)  
● Silicone's rubber  
● Fluorelastomer (Viton)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
Design in accordance with "International Standard ISO 4126-1 Safety Valves".

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
Design in accordance with "ASME code section VIII Div.1".  
Materials according ASME code section II and ASTM. Connections according ASME B1.20.1 standard.

Depending on version

-60°C to +200°C 0,20 bar to 36,00 bar Steam / Gases / Liquids

Depending on version

-76°F to +392°F 2,90 psi to 522,14 psi Steam / Gases / Liquids

