

# Safety

## Full lift safety valve with spring loading. (AIT)



EP AP ES AS

### Mod. 895 EN CRYOGENIC

Connection: Male thread x Female thread  
MR1 x FR2: 3/8"x1/2" to 1"x1"  
Material: ■ Bronze. PMS-36 bar  
■ Stainless steel. PN-40  
Seal: ○ PTFE (Teflon)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
Design in accordance with "International Standard ISO 4126-1:2004 Safety Valves".

Depending on version

 -196°C to +200°C  
 0,20 bar to 36,00 bar  
 Steam / Gases / Liquids



EP AP ES AS

### Mod. 885 EN CRYOGENIC

Connection: Male thread NPT x Female thread NPT  
MNPT1 x FNPT2: 3/8"x1/2" to 1"x1"  
Material: ■ Bronze. PMS-522,14 psi  
■ Stainless steel. 300 lbs  
Seal: ○ PTFE (Teflon)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.  
Design in accordance with "ASME code section VIII".  
Materials according ASME code section II and ASTM.  
Connections according ASME B1.20.1 standard.

Depending on version

 -320,8°F to +392°F  
 2,90 psi to 522,14 psi  
 Steam / Gases / Liquids