

STUDIO 44

CARPET TILE & PLANK



FUNK Specification Sheet

Construction - Tufted

Backing - Vinyl

Dye Method - Solution Dyed

Fiber Type - PET

Fiber Weight - 20oz (407 g/m²)

Plank Pile Density - 6,200

Tile Pile Density - 5,700

Product Size (Plank)- 9.84" x 39.37" (25cm x 100cm)

Thickness - 1/4" (6mm)

Gauge - 1/10

Warranties

10 Year Limited Commercial Warranty

10 Year Limited Surface Wear Warranty

10 Year Limited Static Protection Warranty

10 Year Limited Edge Ravel Warranty

10 Year Limited Dimensional Stability Warranty

10 Year Limited Backing Separation Warranty

Installation Methods

Plank: Quarter Turn, Brick, Ashlar Monolithic,
Random, Herringbone

| Standard | Description | Result |
|----------------------|-----------------------------|-----------------------------|
| ASTM E648 | Flamability | Class 1 |
| ASTM 662 | Smoke Density | Optical Density <450 Passes |
| AATCC-134 | Static Propensity | Under 3.5 KV |
| ASTM F925 | Stain & Chemical Resistance | Passes |
| IAQ Green Label Plus | Green Label Plus 1098 | |

The Gateway Surfaces logo is positioned in the lower-left corner of the image. The background is a vibrant, abstract pattern of swirling colors in shades of orange, yellow, and blue, resembling a marbled or stone surface. The text "gatewaysurfaces" is written in a large, lowercase, sans-serif font across the bottom of the image.