

CENTER



SPC CLICK PLANK

12mil and 20mil wear layer

STAGE

Specification Sheet

Gateway Center Stage SPC Click LVT is offered in two wear layer thicknesses (12mil and 20mil) to cater to the needs of your space. It features crisp wood plank visuals and a high quality, clear, and durable Gateway Guard AO wear surface. The attached pad reduces noise while providing added comfort. Center Stage is an easy-maintenance, water proof flooring option for a variety of residential and commercial applications.

Construction:	5.0mm SPC Click Vinyl Plank with pad (Phthalate Free)
Dimensions / Thickness:	7" x 48" nominal / 5.0mm (4mm + 1mm IXPE pad)
Wear Layer Thickness:	12 mil and 20mil wear layer
Format:	Click Plank
Bevel Type:	Microbevel
Sq. Ft. / Carton	23.78
Cartons / Palett	55

Standard	Description	Result
ASTM E648 - 06	Critical Radiant Flux	Class 1
ASTM E662	Smoke Density	Optical Density <450 Passes
ASTM F1700-13 (F3261 SPC)	Class III Solid Vinyl Tile	Passes
ASTM F925	Stain & Chemical Resistance	Passes
ASTMF970-07	Static Load Resistance	>1400 PSI
ASTM F1514	Heat Stability of Color	Passes
ASTM 1515	Light Stability	Passes
ASTM F386-11	Overall Thickness	Passes
ASTM F3261 (F1914)	Indentation	Passes
ASTM F2055	Size & Squareness	Passes
ASTM C1028	Slip Resistance	Passes ADA Compliance
NALFA 3.5	Large Ball Impact	Class 4 Heavy Commercial
NALFA 3.6	Small Ball Impact	Class 4 Heavy Commercial
ASTM E492-9	Acoustic Rating	IIC 62 6" Concrete Slab & Ceiling
Density	Mass	1900-2100 g/cm3

