# **TYCOON**












## **TYCOON**



12" x 24" Rectified



Additional Information: Tycoon is a rectified monocalibrated color body, glazed porcelain tile, made in the USA. It's design inspiration is taken from Portuguese Limestones quarried in Central Portugal. The limestone from this region exhibits fine grains and soft movements, similar to the Moca Cream and Moleanos that are from the region. The series is available in four neutral colors in both warm and cool tones, perfect for today's marketplace. It provides for an incredible canvas that allows expressive design to go in a variety of directions. The series is suited for both residential and commercial applications with sizes suited for both small and large projects alike. The design faces for each format are as follows: 12x24 (30), 24x48 (10). Tycoon also exceeds the ADA recommendation for slip resistance with a DCOF rating > 0.42.

#### Technical Specifications

2" x 2"

Mosaic

#### This product meets or exceeds all standards described in ANSI A137.1.

	SPECS	TEST METHOD	INDUSTRY STANDARD	MILE®STONE VALUES	
	WATER ABSORPTION	ASTM C373	≤0.5%	≤0.4%	
^	CHEMICAL RESISTANCE	ASTM C650	A tile sample is placed in continuous contact with a variety of chemicals for 24 hours.  No sample must showvisible defects.	NOT AFFECTED	
*	D.C.O.F. AcuTest®	ANSI A326.3	≥0.42% WET	≥0.42% WET	
×	STAIN RESISTANCE	ASTM C1378	Surfaces are exposed to staining agents for 24 hours followed by four cleaning procedures. Results are recordedpost cleaning.	NOT AFFECTED	
۵	BREAKING STRENGTH	ASTM C648	≥250 lb/ft²	8mm≥300 lb/ft² 10mm≥400 lb/ft²	
**	RESISTANCE TO FREEZE	ASTM C1026	A tile sample is subjected to repeated processes of freezing and thawing.  Sample must show no visible defects.	RESISTANT	

<sup>•</sup> Due to the inherent nature of fired porcelain tile, it is important to note that the coefficent of friction may vary within and between product runs

### Packaging Specifications

SIZES		THICKNESS (MM)	PIECES PERBOX	UOM PER BOX	WEIGHT PER BOX	BOXES PER PALLET	UOM PER PALLET	WEIGHT PER PALLET*			
FIELD TILES											
12"x24" RECTIFIED	NOMINAL	8 mm	8	16 SF	52.8	48	768 SF	2,534			
24"x48" RECTIFIED NOMINAL		10 mm	2	16 SF	76.8	32	512 SF	2,457			
MOSAIC AND COORDINATING TRIMS											
12"x12" MOSAIC (2"x2" - 36 DOT)	NOMINAL	8 mm	10	10 PCS	33	45	450 PCS	1,485			

<sup>\*</sup>WEIGHT PER PALLET DOES NOT INCLUDE pallet WEIGHT itself. All other sizes will be packaged as ordered.

Please contact MILESTONE Customer Service at 1-877-356-7461 for packaging information.

Minimum grout size recommended = 5 mm (or approx. 3/16") If staggered tile placement, we recommend using a 30% offset. If specified brick pattern with 1/2 pattern mandatory, a bigger grout is recommended to hide imperfections of installation (minimum 1/4").

Green Memberships & Accreditations



























