MT. ROYALETM

GLAZED PORCELAIN













MT. ROYALE™

GLAZED PORCELAIN

6 x 36 PRESSED



Natural



Walnut



Gray

SIZES

		SQ. FT./ CARTON	PIECES/ CARTON	CARTONS/ PALLET	SQ. FT./ PALLET	LBS/ CARTON
6 x 36 Pressed	(5-7/8" x 35-7/16") (15.00 cm x 90.00 cm)	13.05	9	48	626.4	54.027

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	•
Wet & Level – Interior Floor	≥ 0.42	•
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	•
Countertops	N/A	•
Pool Linings	N/A	

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.



Pecan



Gunstock

INSTALLATION

_	GROUT JOINT RECOMMENDATION	SHADE VARIATION
	3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	V3 High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	III

USAGE

F	W	С	
FLOORS	WALLS	COUNTERTOPS	























