

Uptown

pan
american
ceramics





LEAD
Structured Semi-Pol 12"x24"



LEAD MOSAIC
12"x12"



LEAD 12"x24"



LEAD 24"x24"



LEAD 18"x36"



SILVER
Structured Semi-Pol 12"x24"



SILVER MOSAIC
12"x12"



SILVER 12"x24"



SILVER 24"x24"



SILVER 18"x36"



GREIGE
Structured Semi-Pol 12"x24"



GREIGE MOSAIC
12"x12"




GREIGE 12"x24"



GREIGE 24"x24"



GREIGE 18"x36"



GREIGE BULLNOSE 3"x24"
SILVER BULLNOSE 3"x24"
LEAD BULLNOSE 3"x24"



MULTIDEKOR GREIGE
(4 Random Deco Designs) 12"x24"

Technical data conform to:

	Abrasion resistance	ISO 10545-7	PEI V		Stain resistance	ISO 10545-14	Complete
	Breaking modulus	ISO 10545-4	40±55 N/mm ²		Slipperiness	DIN 51130	R10
	Mohs hardness	EN101	6		Slipperiness	ASTM C1028	WET > 0,64 DRY > 0,75
	Glaze resistance to acid and alkaline attack	ISO 10545-13	Resists		Slip resistance	DIN 51097	B
	Resistance to frost	ISO 10545-12	Frost proof		Slipperiness B.C.R.A.	TORTUS	WET > 0,58 DRY > 0,69
					Water absorption	ISO 10545-3	≤ 0,1%

Packing

SIZE	PCS/CTN	SF/CTN	CTN/PAL	SF/PAL	LBS/CTN	THICKNESS
field 18"x36"	3	13.35	32	427.2	64.14	10 mm
field 24"x24"	4	15.5	30	465	70.6	10 mm
field 12"x24"	5	9.7	40	388	47.5	10 mm
structured semi-pol 12"x24"	5	9.7	40	388	47.5	10 mm
multidekor 12"x24"	5				47.5	10 mm
mosaic 12"x12"	4				17	10 mm
bullnose 3"x24"	12				33	