






BEIGE CIRCLE Rett.
25x25 10"x10"



BEIGE PAINT Rett.
25x25 10"x10"



BEIGE GEO Rett.
25x25 10"x10"




BEIGE RUG Rett.
25x25 10"x10"



GREY CIRCLE Rett.
25x25 10"x10"



GREY PAINT Rett.
25x25 10"x10"



GREY GEO Rett.
25x25 10"x10"



GREY RUG Rett.
25x25 10"x10"



IVORY PLAIN Rett.
25x25 10"x10"

Tecnical data conform to: EN 14411 B1. GL			COMFORT C				COMFORT C
	Abrasion resistance	ISO 10545-7	PEI III / PEI IV		Stain resistance	ISO 10545-14	Complete
	Water absorption	ISO 10545-3	≤ 0,5%		Slipperiness	DIN 51130	R10
	Breaking modulus	ISO 10545-4	40:55Nmm2		Slip resistance	DIN 51097	B
	Resistance to frost	ISO 10545-12	Frost proof		Slipperiness	ANSI A137-1	> 0,42
	Glaze resistance to acid and alkaline attack	ISO 10545-13	Resists		Slipperiness B.C.R.A.	TORTUS	> 0,40

Packing SIZE	PCS/CTN	SF/CTN	LBS/CTN	CTN/PLT	SF/PAL	THICKNESS
10"x10" rett.	16	10,76	48,94	63	677,25	9,985mm