

TEMPER
GLAZED PORCELAIN TILE

COLORS				
Finish: Matte				
Look: Concrete				
Rectified				
	ASHEN	COOL GRAY	SLATE	STONE

SIZES	24"x48" Field Tile	12"x24" Field Tile	3"x24" Bullnose	6" Hex 10"x11.5" Mosaic	2" Hex 12"x12" Mosaic	2"x2" 12"x12" Mosaic
Thickness	10.3 mm	8.4 mm	8.4 mm	8.4 mm	8.4 mm	8.4 mm
Pcs / Carton	2	8	15	10	10	10
Sq. Ft. / Carton	15.5	15.5	n/a	7.97	9.69	9.58

TECHNICAL SPECS	DESCRIPTION	METHOD	UNIT	VALUES
	WATER ABSORPTION	EN 99, ISO 10545-3, ASTM C373-88	%	≤0.4
	ABRASION RESISTANCE	EN 154, ISO 10545-7, ASTM C1027-99	PEI	Class 4
	SCRATCH HARDNESS	EN 101, ISO 10545-6	MOHS	9
	BREAKING STRENGTH	ISO 10545-4, ASTM C648	LBF N	>400 >1750
	CHEMICAL RESISTANCE	ISO 10545-13		Class A
	STAIN RESISTANCE	EN 122, ISO 10545-14		Class 5
	FROST RESISTANT	EN 202, ISO 10545-12, ASTM C1026		Pass
	SLIP RESISTANCE	ANSI A 137.1	DCOF (Wet)	≥0.50
		DIN 51130	R	R 10
	SHADE VARIATION			V2

DISCLAIMER: Tech values represent Field Tiles. Multiple values indicate differences due to size and/or finish.

The American Society for Testing and Materials (ASTM), the International Organization for Standardization (ISO), German Institute for Standardization (DIN), American National Standards Institute (ANSI) and the EU ISO are internationally recognized organizations that identify industry test methods and technical standards. All tests are subject to change based on new studies and standards may vary across different industry procedures.