











**CREST**  
GLAZED PORCELAIN TILE

COLORS

			
MONATH	MARIA	WANING	WAXING
			
MONATH MURETTO	MARIA MURETTO	WANING MURETTO	WAXING MURETTO

**Finish:** Matte

**Look:** Stone

SIZES	24"x24" Field Tile	12"x24" Field Tile / Muretto	8"x24" Field Tile	4"x12" Field Tile	2"x2"  12"x12" Mosaic	2"x8" Bullnose	3"x12" Bullnose
Thickness	8.8 mm	8.8 mm	9.2 mm	9.2 mm	8.8 mm	9.2 mm	8.8 mm
Pcs / Carton	4	8	14	24	5	24	30
Sq. Ft. / Carton	15.5	15.5	18.3	7.1	0	0	0

TECHNICAL SPECS	DESCRIPTION	METHOD	UNIT	VALUES
	WATER ABSORPTION	EN 99, ISO 10545-3, ASTM C373-88	%	<0.5%
	ABRASION RESISTANCE	EN 154, ISO 10545-7, ASTM C1027-99	PEI	4
	SCRATCH HARDNESS	EN 101, ISO 10545-6	MOHS	3   4
	BREAKING STRENGTH	ISO 10545-4, ASTM C648	N	>=1300N   >=600
	CHEMICAL RESISTANCE	ISO 10545-13		Class A
	STAIN RESISTANCE	EN 122, ISO 10545-14		Class 5   Class 4
	FROST RESISTANT	EN 202, ISO 10545-12, ASTM C1026		Pass
	SLIP RESISTANCE	ANSI A 137.1	DCOF (Wet)	
		DIN 51130	R	R9
SHADE VARIATION			V3	

**DISCLAIMER:** Tech values represent Field Tiles. Multiple values indicate differences due to size and/or finish.

The American Society for Testing and Materials (ASTM), the International Organization for Standardization (ISO), German Institute for Standardization (DIN), American National Standards Institute (ANSI) and the EU ISO are internationally recognized organizations that identify industry test methods and technical standards. All tests are subject to change based on new studies and standards may vary across different industry procedures.