

Plank Size (Length x Width x Height)	Edge Profile	Finish	Underlayment	Wear layer	Gloss Level	Installation	Radiant Heat	
60 in x 9 in 1524 X 228 X 8mm	V-groove	EIR	-	AC5	6-8°	Floating	Approved	
WARRANTY		PACKAGING						
Residential	Commercial	Length	Planks Per Carton	Square Footage Per Carton	Carton Dimensions (Length x width x Height)	Carton Weight	Cartons Per Pallet	Square Footage Per Pallet
30 Years	10 Years	60"	5	18.70 SF	1528 x 232 X 42mm	23.9 KG	48	897.65 SF
TESTING								
Reference	ASTM Norms		Test Request			Result		
Impact Sound Reduction (IIC)	ASTM E492-09		Based on actual data		Based on actual data		IIC=62*	
Sound Transmission Class (STC)	ASTM E90-09		Based on actual data		Based on actual data		STC=63*	
*Sound Ratings were achieved in a lab environment. For accurate sound ratings, on-site testing must be done.								
Reference Residual	ASTM Norms ASTM		Test Request Average:Avg. ≤ 0.007 in. (0.18			Result		
Indentation	F3261-17		mm)			Pass		
Static Load Limit	ASTM F3261-17		max loading: 250 lb/in.2 (1.72mpa)			Pass		
Dimensional Stability	ASTM F3261-17		0.2% / lineal ft (305mm), max			Pass		
						Pass		
Curling	ASTM F3261-17		Max 0.080 in. (2mm)			Pass		
Scratch Resistance	ISO 1518-1:2011		No penetration with 20N			Pass		
Fire test - Critical radiant flux	ASTM E 648-17a		Critical Radiant Flux, watts/cm <sup>2</sup> Class I ≥ 0.45			Pass		
Migration of Certain Elements	EN 71-3: 2013+A2:2017		Not Detected			Pass		
Migration of Certain Elements Refer to Annex A								