

FICHA TÉCNICA DATA SHEET

GOLDEN HILL

PORCEMALL

PE

PORCELÁNICO ESMALTADO
GLAZED PORCELAIN TILE



SATINADO
SATIN

RC

RECTIFICADO
RECTIFIED



DIFERENTES GRÁFICAS
DIFFERENT PRINTINGS



White

Formato / Size	Mármol / Marble	Grupo / Group	Tipo / Type
100x100 / 40"x40" 60x120 / 24"x48"		Bib	Porcelánico esmaltado / Glazed Porcelain Tile

UNE-EN 14411:2016

DESCRIPCIÓN DEL TEST / TEST DESCRIPTION	NORMA / STANDARD	VALOR DEL TEST / TEST VALUE	Porcemall
Absorción de agua / Water absorption	UNE-EN-ISO 10545-3	0,5% < Ev ≤ 3 %	Cumple / Complies
Fuerza de rotura / Breaking strength	UNE-EN-ISO 10545-4	≥ 1100 N	Cumple / Complies
Resistencia a la flexión / Resistance of flexion	UNE-EN-ISO 10545-4	≥ 30 N/mm ²	Cumple / Complies
Abrasión superficial / Surface abrasion	UNE-EN-ISO 10545-7	Valor declarado / Declared value	según modelo / according to model
Resistencia al cuarteo / Cracking resistance	UNE-EN-ISO 10545-11	Requerido / Requested	Cumple / Complies
Resistencia a la helada / Frost resistance	UNE-EN-ISO 10545-12	Requerido / Requested	Cumple / Complies
Resistencia química / Chemical resistance	Productos domésticos y aditivos piscina / Household chemicals and swimming pool salts	UNE-EN-ISO 10545-13	Mínimo clase B / Minimum class B
	Ácidos a baja concentración/ / Low concentration of acids	UNE-EN-ISO 10545-13	Valor declarado / Declared value
	Bases a baja concentración/ / Low concentration of alkalis	UNE-EN-ISO 10545-13	Valor declarado / Declared value
Resistencia a las manchas / Resistance to stains	UNE-EN-ISO 10545-14	Mínimo clase 3 / Minimum class 3	Cumple / Complies
Resistencia al deslizamiento / Slip resistance	UNE-41901 EX Péndulo / Pendulum		-
	BS 7976-2:2002+A1:2013 Resistencia al deslizamiento (Péndulo) : Método operativo (PTV)/ Slip resistance (Pendulum): Pendulum test value (PTV)		-
	ANSI A137. 1:2017. 9.6 Coeficiente de fricción dinámico (D.C.O.F./ Dynamic coefficient of friction (D.C.O.F)		-
	DIN 51130:2014-5 Ángulo crítico deslizamiento (Rampa)/ Critical angle of slip (Inclined platform)		-
	DIN 51097 Ángulo crítico deslizamiento zonas húmedas de andar descalzo/ Critical angle of slip wet-loaded barefoot areas		-
Resistencia al rayado / Hardness (MOHS)	EN-101	Valor declarado / Declared value	Mínimo 3 / Minimum 3