

Plank Size (Length x Width x Height)		Edge Profile	Finish	Underlayment	Wear layer	Gloss Level	Installation	Radiant Heat
60 in x 9 in 1524 X 228 X 8mm		V-groove	EIR	-	AC5	6- 8°	Floating	Approved
WARRANTY		PACKAGING						
Residential	Commercial	Length	Planks PerCarton	Square Footage Per Carton	Carton Dimensions (Length x width x Height)	Carton Weight	Cartons Per Pallet	Square Footage Per Pallet
30 Years	10 Years	60"	9	34.48 SF	1528 x 232 X 42mm	43.02 KG	40	897.65 SF
TESTING								
Reference				ASTM Norms		Test Request		Result
Impact Sound Reduction (IIC)				ASTM E492- 09		Based on actual data	Based on actual data	IIC=62*
Sound Transmission Class (STC)				ASTM E90- 09		Based on actual data	Based on actual data	STC=63*
*Sound Ratings were achieved in a lab environment. For accurate sound ratings, on- site testing must be done.								
Reference Residual				ASTM Norms ASTM		Test Request		Result
Indentation				F3261- 17		Average:Avg. ≤ 0.007 in. (0.18 mm)		Pass
Static Load Limit				ASTM F3261- 17		max loading: 250 lb/in.2 (1.72mpa)		Pass
Dimensional Stability				ASTM F3261- 17		0.2%/ lineal ft (305mm), max		Pass
								Pass
Curling				ASTM F3261- 17		Max 0.080 in. (2mm)		Pass
Scratch Resistance				ISO 1518- 1:2011		No penetration with 20N		Pass
Fire test - Critical radiant flux				ASTM E 648- 17a		Critical Radiant Flux, watts/cm2 Class I≥ 0.45		Pass
Migration of Certain Elements				EN 71- 3:2013+A2:2017		Not Detected		Pass
Migration of Certain Elements Refer to Annex A								