

PRODUCT: **PORCELAIN GLAZED POLISHED**

PRODUCTION NORM: **ISO 13006**

TIPY: **Bla**

NOMINAL SIZE: **120X120 CM**

WORK SIZE: **1200X1200 MM**

THICKNESS: **9 MM**

### 1. Dimensions and Surface Quality - ISO 10545

TECHNICAL FEATURES		SPECIFICATIONS	UNIT	AVARAGE	STANDART
1.1 Length		± 0,6% MAX	mm	1199,28 ~ 1200,72	ISO-10545-2
1.2 Whidth		± 0,6% MAX	mm	1199,28 ~ 1200,72	
1.3 Thickness		± 5% MAX.	mm	8.55 ~ 9,45	
1.4 Straightness of sides		± 0,5% MAX	mm	- 0,60 ~ + 0,60	
1.5 Regularity		± 0,5% MAX	mm	- 0,60 ~ + 0,60	
1.6 Surface flatness	1.6.1 Centre curvature	± 0,5% MAX	mm	- 0,60 ~ + 0,60	
	1.6.2 Edge curvature	± 0,5% MAX	mm	- 0,60 ~ + 0,60	
	1.6.3 Warpage (vs diagonal)	± 0,6% MAX	mm	- 1,00 - + 1,00	
1.7 Surface quality		95	%	95	

### 2. Physical Properties - ISO 10545

2.1 Water absorption		≤ 0,5	%	0,5	ISO-10545-3
2.2 Modulus of Rupture		≥ 35	N/mm <sup>2</sup>	38	ISO-10545-4
2.3 Deep Abrasion Resistance		1 a 5	PEI	4	ISO-10545-7
2.4 Thermal shock resistance		RESISTANT (YES/NO)	-	RESISTANT	ISO-10545-9
2.5 Frost resistance		RESISTANT (YES/NO)	-	RESISTANT	ISO-10545-12
2.6 Static coefficient of friction (SCOF)	2.6.1 Dry	μ>0.4	-	μ>0.6	ASTM-C1028
	2.6.2 Wet	μ<0.4	-	μ<0.6	
Dinamic coefficient of friction (DCOF)		< 0,4 - SLIP > 0,4 Anti SLIP	-	< 0,4 -SLIP	ANSI A 137-1, Section 9.6

### 3. Chemical Properties - ISO 10545

3.1 Resistance to chemicals		Ubmin	-	GLA	ISO-10545-13
3.2 Resistance to staining		1 a 5 1- Impossible to eliminate 5- Maximum ease	-	5	ISO-10545-14

### 4. Shade Variation

	V1 a V4	V2	ANSI A 137-1, Section 5.4.2
--	---------	----	--------------------------------

### 5. Acceptande of Supplier

Acknowledgment and acceptance of the terms and requirements defined or referenced in this Technical Specification.

Company: **Porcemall USA Corp**

Name: **Archt. Ricardo Porto**

Title: **Quality Control Director**

Signature:



Date: **April 05, 2023**