

# PRESTIGE 48"X48"

## Matt



### PRIS.PRESTIGE

|                                |                               |
|--------------------------------|-------------------------------|
| FORMATO/ <i>FORMAT</i>         | 120X120                       |
| ESPESOR/ <i>THICKNESS</i> (mm) | 10,7                          |
| PRODUCTO/ <i>PRODUCT</i>       | PORCELANICO/ <i>PORCELAIN</i> |
| TIPO/ <i>KIND</i>              | ESMALTADO/ <i>GLAZED</i>      |
| GRUPO/ <i>GROUP</i>            | Bla - GL                      |

NORMA APLICABLE EN 14411 ANEXO G  
*APPLICABLE STANDARD ISO 13006 ANNEX G*

| ENSAYOS/ <i>TESTS</i> |                                                                                              | RESULTADOS/ <i>RESULTS</i>                                               |                                                          |
|-----------------------|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|----------------------------------------------------------|
|                       | UNE-EN ISO 10545-2 DIMENSIONES Y ASPECTO SUPERFICIAL                                         | DIMENSIONES                                                              | CUMPLE CON LA NORMA                                      |
|                       | <i>UNE-EN ISO 10545-2 DIMENSIONS AND SURFACE QUALITY</i>                                     | <i>DIMENSIONS</i>                                                        | <i>COMPLIES WITH THE STANDARD</i>                        |
|                       | UNE-EN ISO 10545-3 ABSORCIÓN DE AGUA                                                         | VALOR MEDIO (%)                                                          | ≤ 0,5 %                                                  |
|                       | <i>UNE-EN ISO 10545-3 WATER ABSORPTION</i>                                                   | <i>AVERAGE VALUE (%)</i>                                                 |                                                          |
|                       | UNE-EN ISO 10545-4 RESISTENCIA A LA FLEXIÓN<br><i>UNE-EN ISO 10545-4 MODULUS OF RUPTURE</i>  | FUERZA DE ROTURA                                                         | 1.600 - 2.400 N                                          |
|                       |                                                                                              | <i>BREAKING STRENGTH (N)</i>                                             |                                                          |
|                       |                                                                                              | RESISTENCIA A LA FLEXIÓN<br><i>MODULUS OF RUPTURE (N/mm<sup>2</sup>)</i> | 35 – 45 N/mm <sup>2</sup>                                |
|                       | UNE-EN-ISO 10545-7 ABRASIÓN SUPERFICIAL (PEI)                                                | RESULTADO                                                                | PEI 4                                                    |
|                       | <i>UNE-EN-ISO 10545-7 SURFACE ABRASION (PEI)</i>                                             | <i>RESULT</i>                                                            |                                                          |
|                       | UNE-EN ISO 10545-9 RESISTENCIA AL CHOQUE TÉRMICO                                             | RESULTADO                                                                | RESISTE                                                  |
|                       | <i>UNE-EN ISO 10545-9 THERMAL RESISTANCE</i>                                                 | <i>RESULT</i>                                                            | <i>RESISTS</i>                                           |
|                       | UNE-EN-ISO 10545-11 RESISTENCIA AL CUARTEO                                                   | RESULTADO                                                                | RESISTE                                                  |
|                       | <i>UNE-EN-ISO 10545-11 CRAZING RESISTANCE</i>                                                | <i>RESULT</i>                                                            | <i>RESISTS</i>                                           |
|                       | UNE-EN ISO 10545-12 RESISTENCIA A LA HELADA                                                  | RESULTADO                                                                | RESISTE                                                  |
|                       | <i>UNE-EN ISO 10545-12 FROST RESISTANCE</i>                                                  | <i>RESULT</i>                                                            | <i>RESISTS</i>                                           |
|                       | UNE-EN ISO 10545-13 RESISTENCIA QUÍMICA<br><i>UNE-EN ISO 10545-13 CHEMICAL RESISTANCE</i>    | CLORURO AMÓNICO                                                          | A                                                        |
|                       |                                                                                              | <i>AMMONIUM CHLORIDE 100 g/l</i>                                         |                                                          |
|                       |                                                                                              | HIPOCLORITO SÓDICO                                                       | A                                                        |
|                       |                                                                                              | <i>SODIUM HYPOCHLORITE 20 mg/l</i>                                       |                                                          |
|                       |                                                                                              | ÁCIDO CLORHÍDRICO                                                        | CUMPLE CON LA NORMA<br><i>COMPLIES WITH THE STANDARD</i> |
|                       |                                                                                              | <i>HYDROCHLORIC ACID 3%</i>                                              |                                                          |
|                       |                                                                                              | ÁCIDO CÍTRICO                                                            |                                                          |
|                       |                                                                                              | <i>CITRIC ACID 100 g/l</i>                                               |                                                          |
|                       | UNE-EN ISO 10545-14 RESISTENCIA A LAS MANCHAS<br><i>UNE-EN ISO 10545-14 STAIN RESISTANCE</i> | HIDRÓXIDO POTÁSICO                                                       | 5                                                        |
|                       |                                                                                              | <i>POTASSIUM HYDROXYDE 30 g/l</i>                                        |                                                          |
|                       |                                                                                              | ÓXIDO VERDE EN ACEITE LIGERO                                             | 5                                                        |
|                       |                                                                                              | <i>GREEN AGENT IN LIGHT OIL</i>                                          |                                                          |
|                       |                                                                                              | SOLUCIÓN ALCOHÓLICA DE YODO                                              | 5                                                        |
|                       |                                                                                              | <i>IODINE SOLUTION IN ALCOHOL</i>                                        |                                                          |
|                       |                                                                                              | ACEITE DE OLIVA                                                          | 5                                                        |
|                       |                                                                                              | <i>OLIVE OIL</i>                                                         |                                                          |

OBSERVACIONES:

VºBº LABORATORIO:

